

CERTIFIKAT

TYPE EXAMINATION CERTIFICATE No. 34 48 01

Ladders

Holder/ Manufacturer/Supplier

Telesteps AB, Box 362, SE-573 24 Tranås, Sweden.

Product name

Telesteps

Product description

Telescopic ladders and working platform made of aluminium as described in the appendix to this certificate. Technical documentation in accordance with the material supplied for SP file reference P600696.

Requirements

The Swedish National Board of Occupational Safety and Health's Code AFS 2004:3 Ladders and trestles, (SP's certification rules SPCR 064), SS 2091 Edition 4 and EN 131 Part 1 and 2

Marking

The ladders and the stepladders shall be marked with the SP-mark (below), number of the certificate (34 48 01), name or logotype of the holder/manufacturer/supplier, type of ladder (according to SS 2091), year of manufacture (2 digits) and month- alternatively serial number and number of persons who may enter the product at the same time.

Validity

This certificate is valid until 17th September 2012

Miscellaneous

This certificate replaces earlier certificate with the same number, dated 17th April 2007. The certificate has originally been issued 17th September 2002.

This is a translation from the Swedish original document. In the event of any dispute as to the content of the document, the Swedish text shall take precedence.

Borås, 15th November 2007

SP Technical Research Institute of Sweden

Certification

Lennart Månsson Certification manager Sunnar Söderlind Certification Officer



1002 EN 45 011



Type examination certificate issued by an accredited certification body

SWEDEN



Appendix to TYPE EXAMINATION CERTIFICATE

No 34 48 01 dated 15th November 2007

Signed for SP:

Product list of Telesteps telescopic ladders

Type of ladder	Art.No.	Length (m)	Deep of step (mm)
Single rung ladder	50120	2.0	40
	50126	2.6	40
	50130	3.0	40
	50133	3.3	40
	50138	3.8	40
	60120	2.0	40
	60126	2.6	40
	60133	3.3	40
	60135	3.5	40
	60220	2.0	65
	60226	2.6	65
	60233	3.3	65
	60235	3.5	65
	60735	35	40
	60738	3.8	40
	60835	3.5	65
	60838	3.8	65
	61435	3.5	65
Freestanding rung	60414	1.45	65
Ladder	60511	1.15	40
	60517	1.75	40
Freestanding step	60411	1.15	90
Ladder	60417	1.75	90
Combination ladder	60617	1.7	90
	60620	2.0	65
	60623	2.3	90
	60630	3.0	90
Working platform	61109	0.88	65
	61209	0.88	65
	61309	0.88	65

Conditions

- Before each use, the ladder shall be checked in terms of correct locking.
- The ladder may not be used at dirty work or in dirty environments. Use at bricklaying, concrete works, painting etc. will make the ladder difficult to clean. This may lead to a heavy deterioration of the telescopic function.





Appendix, page 1(2)

SWEDEN



Appendix to TYPE EXAMINATION CERTIFICATE

No 34 48 01 dated 15th November 2007

Signed for SP:

Erection instructions must be supplied with the ladder when it is handed over to the user. The
instructions shall show that if the marking has become hardly legible, new marking can be
ordered.

Miscellaneous

This type examination certificate is valid for ladders made and supplied by the manufacturer and supplier as stated on the certificate, and of which the materials, dimensions and design/construction accord with those of the inspected material.



1002 EN 45011



Appendix, page 2(2)

SWEDEN